



SPECIFICATIONS

UNSTIFFENED HOPPER BINS

Bin Diameter	Rings	Eave Height (ft)	Peak Height (ft)	Max Bushel Capacity*	METRIC			
					Eave Height (Meters)	Peak Height (Meters)	Max Capacity* (Cubic Meter)	Max Capacity* (Metric Tons)
15' (4.57 m)	3	11' 1"	15' 4"	1,836	3.38	4.67	61	50
	4	14' 9"	19' 0"	2,382	4.50	5.79	79	65
	5	18' 5"	22' 8"	2,929	5.61	6.91	97	80
	6	22' 1"	26' 4"	3,475	6.73	8.03	115	95
18' (5.49 m)	3	11' 1"	16' 6"	2,700	3.38	5.03	90	74
	4	14' 9"	20' 2"	3,487	4.50	6.15	116	95
	5	18' 5"	23' 10"	4,274	5.61	7.26	142	116
	6	22' 1"	27' 6"	5,060	6.73	8.38	168	138
21' (6.40 m)	3	11' 1"	17' 4"	3,753	3.38	5.28	125	102
	4	14' 9"	21' 0"	4,824	4.50	6.40	160	131
	5	18' 5"	24' 8"	5,894	5.61	7.52	196	160
	6	22' 1"	28' 4"	6,965	6.73	8.64	231	190
24' (7.32 m)	3	11' 1"	18' 4"	5,003	3.38	5.59	166	136
	4	14' 9"	22' 0"	6,401	4.50	6.71	213	174
	5	18' 5"	25' 8"	7,800	5.61	7.82	259	212
	6	22' 1"	29' 4"	9,198	6.73	8.94	306	250
27' (8.23 m)	3	11' 1"	19' 1"	6,459	3.38	5.82	215	176
	4	14' 9"	22' 9"	8,229	4.50	6.93	273	224
	5	18' 5"	26' 5"	9,999	5.61	8.05	332	272
	6	22' 1"	30' 1"	11,769	6.73	9.17	391	320

* MAX CAPACITY OF THE HOPPER BIN ONLY. DOES NOT INCLUDE CONE CAPACITY.